



MODEL	2-42001-012, 2-42001-013*	
TORQUE LB.FT.	3/4 OR 3/8	
MAXIMUM RPM	3600	
INERTIA WK ² LB.FT. ²	.001	
WT.LBS. PKG'D	2 1/2	
AIR GAP	MIN.	23/64**
	MAX.	7/16

*MODEL INCLUDES MANUAL RELEASE WITH AUTOMATIC RESET.
 **THE 23/64" MINIMUM AIR GAP IS A NOMINAL POSITION. ON LOW HORSEPOWER UNITS, THE GAP MAY HAVE TO BE SLIGHTLY LARGER. OBSERVE MOTOR STARTING CHARACTERISTICS AFTER ADJUSTING THE GAP. THE MOTOR SHOULD START QUICKLY. IF NOT, INCREASE THE AIR GAP.

THIS MATERIAL IS PROPERTY OF DINGS COMPANY. NO RIGHTS ARE GRANTED TO USE SUCH MATERIAL FOR ANY PURPOSE OTHER THAN (1) PRODUCT EVALUATION OR MAINTENANCE OR (2) THE FURNISHING OF SERVICES AND SUPPLIES TO THE DINGS COMPANY.

TITLE OUTLINE DRAWING 40 SERIES - S4012 & S4013		
TOLERANCE UNLESS OTHERWISE NOTED .000 ± .005 FRACTIONS ± .015 .00 ± .010 ANGLES ± 1°	 4740 WEST ELECTRIC AVE. MILWAUKEE, WISCONSIN 53219 U.S.A. <i>Dings Dynamics Company</i>	
DRN BY JEBr		CRD BY
DATE 8-30-06		SCALE FULL

A	1768	7-17-98	RM	ADDED AIR GAP TO TABLE
REV	CHG#	DATE	BY	REVISION

REFER TO CAD FILE: K040054	DRAWING NO. K040054	REV. NO.
-------------------------------	------------------------	----------