



\*SEE BULLETIN BK4710 FOR OPERATING, INSTALLATION AND PARTS INSTRUCTIONS

MODEL NUMBER	NUMBER OF ROTATING DISCS	TORQUE LB.FT.	THERMAL CAPACITY HPS./MIN.	INERTIA OF ROTATING PARTS LB.FT <sup>2</sup>	MAGNET AIR GAP		DIMENSIONS					COVER MATERIAL	BRACKET MATERIAL
					ORIGINAL SETTING	MAXIMUM	X	G*	AC*	C*	N*±1/32"		
6-61001-545	1	1.5	6	.006	.045/.050	.100	.88	1.19	.59	4.13	1.13	STAMPED STEEL	ALUMINUM
6-61003-545	1	3	6	.006	.045/.050	.100	.88	1.19	.59	4.13	1.13	STAMPED STEEL	ALUMINUM
6-61006-545	1	6	6	.006	.045/.050	.100	.88	1.19	.59	4.13	1.13	STAMPED STEEL	ALUMINUM
6-62006-545	2	6	6	.010	.050/.055	.100	.88	1.19	.59	4.13	1.13	STAMPED STEEL	ALUMINUM
6-62010-545	2	10	6	.010	.050/.055	.100	.88	1.19	.59	4.13	1.13	STAMPED STEEL	ALUMINUM
6-63010-545	3	10	6	.015	.060/.065	.100	1.19	1.56	.96	4.50	1.44	STAMPED STEEL	ALUMINUM
6-63015-545	3	15	6	.015	.060/.065	.100	1.19	1.56	.96	4.50	1.44	STAMPED STEEL	ALUMINUM
6-63020-545	3	20	6	.015	.060/.065	.100	1.19	1.56	.96	4.50	1.44	STAMPED STEEL	ALUMINUM

\*NOTE: WHEN APPLICABLE, TABLE DIMENSIONS ARE REFERENCED FROM THE BRAKE MOUNTING FACE AND DO NOT INCLUDE THE GASKET THICKNESS.

THIS MATERIAL IS PROPERTY OF DINGS COMPANY. NO RIGHTS ARE GRANTED TO USE SUCH MATERIAL FOR ANY PURPOSE OTHER THAN (1) PRODUCT EVALUATION OR MAINTENANCE OR (2) THE FURNISHING OF SERVICES AND SUPPLIES TO THE DINGS COMPANY.

TOLERANCE UNLESS OTHERWISE NOTED  
 .000 ± .005 FRACTIONS ± .015  
 .00 ± .010 ANGLES ± 1°

**DINGS DYNAMICS**  
 4740 WEST ELECTRIC AVE.  
 MILWAUKEE, WISCONSIN 53219 U.S.A.

D 2323	9-25-07	JEBr	INTERNAL WIRE HOLE WAS OPTIONAL	DRN BY	CHKD BY
C 2226	6-30-06	JEBr	UPDATED DRAWINGS	SAT	
B 2065	4-24-02	BH	ADDED MODEL -61006-	DATE	SCALE
A 1920	2-21-00	CS	UPDATED BRACKET	5-21-99	FULL
REV	CHG#	DATE	BY	REVISION	REFER TO
					CAD FILE: L0603442

DRAWING NO. **L060344** SHEET 2 OF 2 REV. NO. D